

EFH Zysset, Thun

2004



This simple, rectangular, Minergie-standard single-family house on a slope did not present a major challenge to the timber engineer from the outside. The difficulty, however, was that the top floor had hardly any walls.

The project

A simple, rectangular single-family house in Minergie standard on a slope.

The construction method

On the south side, a stable box girder of approx. 2 m width was formed over two floors. The structural design of the roof as a folding structure was achieved by means of two trusses in the roof plane. A tension band was used in the recessed facade of the east wall. The walls were designed as timber frame construction, the ceilings as simple beam layers. The façade is a ventilated, beveled and glazed horizontal formwork with 8 mm joints. For the floor-to-ceiling windows, the formwork was pulled through to chest height. However, every second formwork board was omitted, creating a "French balcony."

The challenge

On the north and west sides, the walls could be used for bracing; on the south side, on the other hand, only an approx. 1 m wide wall section was provided, and on the east side no wall at all. In addition, the roof on the east side covered an open terrace by about 3.2 m and could only be braced on the outside with 2 pendulum supports.



Inside



Inside



View



Inside

Construction Data

- Minergie: BE-304
- External formwork 145 m²
- Exterior walls: 98 m²
- Length / width / height: 14.4 m / 5.8 m / 6.2 m
- Useful area: 180 m²
- Roof area 131 m²

Services of Timbatec

- Statics and construction

Timber construction engineers

Timbatec Holzbauingenieure Schweiz AG, Thun
3600 Thun

Architect

Archart GmbH
3634 Thierachern

Timber construction contractor

Boss Holzbau AG
3600 Thun